



KSTAR UPS UA60 - 600VA/360W

Model No: UPS-KSTAR-650V



Price:

Rs. 10,690

Warranty:

2 Years(s) manufacturer warranty.
2 Years Manufacturer Warranty (1 Year For The Battery)

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Type: Line Interactive UPS
- Model: UA60
- Capacity (VA/Watts): 600VA/360W
- Input:Nominal Input Voltage: 220/230/240 Vac
- Input:Operating Voltage Range: 140~300 Vac
- Input:Operating Frequency Range: 50/60 Hz (1±10%) (Auto Sensing)
- Output:Output Voltage Range (Batt. Mode): Simulated Sinewave At Nominal Voltage ±10%
- Output:Frequency Range (Batt. Mode): 50 Hz Or 60 Hz ± 1 Hz
- Output:Transfer Time: Typical 2-6 ms, 10ms Max.
- Output:Waveform (Batt. Mode): Simulated Sinewave
- Battery:Voltage: 12Vdc
- Battery:Battery Type / Number: 12V/7Ah x 1
- Battery:Typical Recharge Time : 4-6 Hours (To 90% Capacity)
- Safety / Protection: Overload And Overcharge Protection
- Indicators: AC Mode, Battery Mode, Load Level, Battery Level
- Alarm:Battery Mode: Sounding Every 10 Seconds
- Alarm:Battery Low: Sounding Every Second
- Alarm:Overload: Sounding Every 0.5 Second
- Alarm:Battery Replacement Alarm: Sounding Every 2 Seconds
- Alarm:Fault: Continuously Sounding
- Environment:Operating Temperature: 0 - 40°C
- Environment:Humidity Range: 0-95 % (Non-Condensing)
- Environment:Noise Level: <40db (1 Meter From Surface)
- Input/Output: UPS Input/Output : 1P+N+E / 1P+N+E (230V 50Hz) Universal Power Outlet, Output Sockets : 02 Nos
- Other Features Part 1: Excellent Microprocessor Control Guarantees High Reliability. (Internal Self-Diagnostic Technology), Boost And Buck AVR For Voltage Stabilization. (Wide Input Range With Two Boost And One Buck Control)
- Other Features Part 2: Auto Restart While Ac Is Recovering. | Cold Start Function. | Off-Mode Charging. | Fast Intelligent Battery Recharge Function. | Generator Compatible.
- Standards: Safety: IEC/EN62040-1;IEC/EN60950-1 | EMC: IEC/EN62040-2;IEC61000-4-2;IEC61000-4-3;IEC61000-4-4;IEC61000-4-5;IEC61000-4-6;IEC61000-4-8
- Dimensions: 101×298×142 W x D x H (mm)
- Weight: 4.3 kg
- Colors: Black
- Other Information: This UPS is specially designed for Personal Computer with multi-functions. Its light weight, compact design perfect fits to the limited working environment. The line of UPS is equipped with two boost and one buck AVR to stabilize wide input voltage range. It is also built-in with DC start function. This function enables the UPS to be started up without AC power supply. It not only offers great comprehensive power protection against surges and spikes, but also provides pure voltage with AC voltage stabilizer.

Date: 2024-10-07 02:56